



Overview

The EZ Gateway M-Bus to Modbus & BACnet (FS-EZX-MBUS-MOD-BAC) is an easy to use, high-performance building and industrial automation protocol gateway for integrators to interface M-Bus products to Modbus and BACnet management systems in commercial buildings, campuses and industrial facilities over Modbus RTU, Modbus TCP/IP, BACnet MS/TP or BACnet/IP protocols. M-Bus products encompass a wide range of applications such as energy, gas, heating, water, VFD drives and PLCs.


The EZ Gateway M-Bus to Modbus & BACnet combines field-hardened M-Bus, Modbus and BACnet protocol drivers with an easy to use configuration interface that, once configured, allows M-Bus devices to be presented as virtual BACnet devices which simplifies commissioning, configuration and troubleshooting. The intuitive web-based interface allows configurations to be built in the field or in the office. Additionally, the configuration profiles can be downloaded and then uploaded to other FieldServer M-Bus applications, simplifying the commissioning and integration process on repeatable applications.


Sierra Monitor’s M-Bus Explorer and Device Profiles apps allow M-Bus devices to be auto-discovered, templated and presented to quickly configure new M-Bus devices. This makes each corresponding M-Bus device into a virtual BACnet device within the EZ Gateway, providing granular visibility and control over each device from within a BACnet management framework. For example, offline / online status is visible at the individual M-Bus device level.

With the EZ Gateway M-Bus to Modbus & BACnet, the integrator or contractor does not need to be a protocol expert, and can minimize configuration and commissioning time, while also reducing ongoing operating and maintenance costs.

EZ Gateway Features and Benefits

- The M-Bus protocol can be converted to the following protocols:
 - Modbus RTU
 - Modbus TCP/IP
 - BACnet MS/TP
 - BACnet/IP
- M-Bus Interoperability:
 - M-Bus Explorer discovers all M-Bus devices in the network, shows the manufacturer details as well as available points, and offers one-click profile generation
 - Device Profiles management enables efficient profile editing, exporting and importing
 - Up to 64 slave devices (max device count based on model)
 - Communication between devices with different baud rates at the same time
 - Virtual nodes allow each M-Bus device connected to a single EZ Gateway to show as unique devices on the BACnet network
- BACnet COV support provides fast data communication while reducing the traffic over a BACnet network
- BACnet BBMD Server support for connecting to remote BACnet networks
- Diagnostics of the devices connected to the network is available via Web Interface
- BTL certified
- **SMC Cloud** registration connects your devices to the cloud, allowing secure remote access for diagnostics, monitoring, alarming and configuration
- On-board diagnostics allow easy troubleshooting for both serial and Ethernet communications





Configuration

The configuration interface is used to discover and configure the M-Bus to Modbus and BACnet connections. Profiles are created for each M-Bus device to be connected to the EZ Gateway. The EZ profile can be used for additional connections on this EZ Gateway or other EZ Gateways. The EZ profiles can be shared amongst anyone using the EZ Gateway.

Specifications *

Environment

Operating Temperature: -40 to 75°C (-40 to 167°F)

Relative Humidity: 5-90% RH non-condensing

Power Requirements

9-30V DC or 12-24V AC

Current Draw: @ 12V

1 Slave: 580 mA

64 Slaves: 980 mA

Physical Dimensions

H x W x D: 4.5 x 2.9 x 1.6 in. (11.5 x 7.4 x 4.1 cm)

Weight: 0.4 lbs (0.2 Kg)

Other

Configuration/Diagnostic Utilities

Capacity (part# / max slave devices):

FS-EZ1-MBUS-MOD-BAC / 16 slave devices

FS-EZ2-MBUS-MOD-BAC / 32 slave devices

FS-EZ3-MBUS-MOD-BAC / 64 slave devices

Table, Wall or DIN Rail Mount

Communication

Baud: 2400, 4800, 9600, 19200, 38400

Start Bit: 7, 8

Ethernet: 10/100 BaseT MDIX

Approvals

TUV Approved to UL 916, EN 60950-1, EN 50491-3
and CSA C22.2 standards

BTL Certified

RoHS Compliant

GOST-R Certified

CE and FCC



* Specifications subject to change without notice

Ordering Information

The EZ Gateway M-Bus to Modbus & BACnet is available in the following models:

- FS-EZ1-MBUS-MOD-BAC 16 slave devices
- FS-EZ2-MBUS-MOD-BAC 32 slave devices
- FS-EZ3-MBUS-MOD-BAC 64 slave devices

Options

The Accessory Kit consists of a power supply, Ethernet cable, screwdriver, DIN rail mount and a USB flash drive with all manuals, data sheets, discovery tool and ENotes.

- FS-8915-36-QS Accessory Kit, PSU 110-220V

BACnet® is a registered trademark of ASHRAE